

# SPECIFICATIONS



Parameter	B Type PTV (Patient Transport Vehicle)	C Type BLS (Basic Life Support)	D Type ALS (Advance Life Support)
Wheel Base	2815mm	2815mm	2815mm
Emission Norm	BS - IV	BS - IV	BS - IV
Engine Capacity	3455cc	3455cc	3455cc
Engine Power	75 kW @ 2800 rpm	75 kW @ 2800 rpm	75 kW @ 2800 rpm
Power Steering	✓	✓	✓
No. of Tyres	4+1	4+1	4+1
Air Conditioning	Optional	Optional	✓
Overall Length mm	5579	5579	5579
Overall Width mm	2000	2000	2000
Automatic Roll-In stretchers Compliant to Type-B	Yes, Qty - 1 or 2 Compliant to Type-C	Yes, Qty - 1 or 2 Compliant to Type-D	Yes, Qty - 1 or 2
Interiors (Panel)	Soft Roof, Sheet Panel	FRP/Non-Permeable Material	FRP/Non-Permeable Material
Bar Light & Public Address System	✗	✓	✓
Revolving Light on top	✓, Blue Beacon Light	✗, Part of Bar Light	✗, Part of Bar Light
Side Blinkers & Flood Lights	✗	✓	✓
Dual Battery	✗	✓	✓
Provision/Space for Medical Equipment	✓	✓	✓
<b>Extra Fitment (Not in Part-1 of AIS-125)</b>			
Oxygen Delivery System Cylinder will be provided	✓, Clamp for mounting Cylinders	✓, with Compartment for O2 Cylinders	✓, with Compartment for O2
IV Bottle Hooks/Space	✓	✓	✓
Scoop Stretcher	✗	✗	✓
Spine Board	✗	✗	✓

- External Graphics as per ambulance code. • Medical Equipment/Medicines are NOT Included in the SML Supply Scope. Provision/Space will be provided
- Oxygen Cylinders are not Included. • Auto Changer Oxygen Supply System with Digital Display is available at Extra cost (for D type)



## SML ISUZU LTD.

S.C.O. 204 -205, Sector 34-A, Chandigarh - 160022  
 Ph.: +91 172-2647700-10 Fax : +91 172-2615111  
 website : [www.smlisuzu.com](http://www.smlisuzu.com) E- mail : [sml.spv@smlisuzu.com](mailto:sml.spv@smlisuzu.com)

AUTHORISED DEALER

SML  
ISUZU


HOSPITAL



AIS-125

# AMBULANCE

EQUIPPED TO CARE



- Fully Compliant to National Ambulance Code AIS-125 (Part-1) • Double Patient Capacity • External Power support for stationary use.